

Express Blast Lite

PRODUCT DESCRIPTION

Express Blast Lite is a single component salt removing, flash rust preventing, and degreasing additive. Use to remove all contaminants including salts, oil, and blast residue. Use this product in conjunction with power washing, power wash after dry abrasive blasting, wet abrasive blasting, or waterjetting. Express Blast Lite is also effective when used with hand tool or power tool cleaning.

DIRECTIONS

- Typically used in both blast water and wash down water cycles.
- Normally used in pressure washers, wet/ slurry and vapor abrasive blast equipment, and ultra high pressure (UHP) water jetting equipment or after dry abrasive blasting.
- Diluted at 50 - 250:1 ratio with water depending on the application, humidity and level of surface contamination. Dilution ratio of 100:1 is most common for blast and wash water cycles (See Mix Ratio and Coverage memos).
- For high humidity environments with highly contaminated substrates, 50:1 dilution ratio may be necessary for both cycles. Typically, a 100:1 ratio is recommended for both cycles. After dry blasting, 50:1 dilution is recommended, except in low humidity and low contamination environments, when 100:1 should be adequate. Testing various dilution ratios may be required until flash rust is eliminated. Dust and other contaminants left after dry and wet abrasive blasting must be removed with Express Blast Lite treated water. It is recommended to power wash with Express Blast Lite treated water at sufficient pressure and flow rates to effectively dislodge dust and contaminants and prevent flash rusting. For degreasing, a 50:1 dilution ratio is generally recommended but a higher concentration (25:1) and possibly increased water pressure may be necessary.